

113 Holographic Transfer Film

DESCRIPTION: Transfer Film

APPLICATION: Holographically embossed metallised polyester film for use as a cold total transfer lamination film. Supplied without adhesive.

MINIMUM ORDER: 3660m² (610mm x 6000m) 14,640m² (1220mm x 12,000m)

General Information	Resistance Properties												
<p>Colour: Silver</p> <p>Gauge: 12 micron PET film</p> <p>Orientation: As specified by customer (see off roll orientation chart).</p> <p>Splices: Flush cut or flagged by request.</p> <p>Labelling: Rolls individually labelled with : material reference, batch number & roll length. Other labelling requirements by request.</p> <p>Packaging: Rolls packed in suitable cardboard boxes held by a core support.</p> <p>Storage: As 113 may be affected by heat, we advise against transporting and storing the product in high temperatures. High levels of humidity may also adversely affect 113. Do not expose to direct sunlight.</p>	<ul style="list-style-type: none"> • Lightfastness – B.W.S 6 • Classed as non-toxic & meets the following standards: <ul style="list-style-type: none"> - CONEG - EN71.3 - BS5665 Part 111 1995 • ASTM F963-96a US CPSC 												
	<table border="1"> <thead> <tr> <th colspan="2" data-bbox="683 1070 1356 1124">Characteristics of Finished Product</th> </tr> </thead> <tbody> <tr> <td data-bbox="683 1124 981 1249">Print Receptivity</td> <td data-bbox="981 1124 1356 1249">Films are generally receptive to most over-ink applications. The customer, however, should check compatibility.</td> </tr> <tr> <td data-bbox="683 1249 981 1303">Release Mechanism</td> <td data-bbox="981 1249 1356 1303">Easy - Medium</td> </tr> <tr> <td data-bbox="683 1303 981 1357">Core Size</td> <td data-bbox="981 1303 1356 1357">25.4mm / 76mm / 152mm</td> </tr> <tr> <td data-bbox="683 1357 981 1451">Standard Roll Length</td> <td data-bbox="981 1357 1356 1451">Up to 915m on 25.4mm core Up to 3000m on 76mm core Up to 30,000m on 152mm core</td> </tr> <tr> <td data-bbox="683 1451 981 1637">Standard Roll Width</td> <td data-bbox="981 1451 1356 1637">Maximum 1220mm. Minimum 15mm . Alternative widths by request.</td> </tr> </tbody> </table>	Characteristics of Finished Product		Print Receptivity	Films are generally receptive to most over-ink applications. The customer, however, should check compatibility.	Release Mechanism	Easy - Medium	Core Size	25.4mm / 76mm / 152mm	Standard Roll Length	Up to 915m on 25.4mm core Up to 3000m on 76mm core Up to 30,000m on 152mm core	Standard Roll Width	Maximum 1220mm. Minimum 15mm . Alternative widths by request.
Characteristics of Finished Product													
Print Receptivity	Films are generally receptive to most over-ink applications. The customer, however, should check compatibility.												
Release Mechanism	Easy - Medium												
Core Size	25.4mm / 76mm / 152mm												
Standard Roll Length	Up to 915m on 25.4mm core Up to 3000m on 76mm core Up to 30,000m on 152mm core												
Standard Roll Width	Maximum 1220mm. Minimum 15mm . Alternative widths by request.												

Data contained in this information sheet is provided as a source of information that we believe to be accurate and reliable but does not constitute a warranty of any kind. Customers should determine to their own satisfaction the suitability of this material for a specific purpose. API reserves the right to change specifications without notice.